

SPEEDWRAP 550

ALUMINIUM, STEEL AND WOOD PROFILES AND PIPES - PVC PROFILE PRODUCTS ETC.

Ask for details



HORIZONTAL STRETCH FILM WRAPPING SERIES

TECHNICAL FEATURES

PRODUCT TO WRAP SIZES

Max. Length		Unlimited	
Max. Width x Max. Height	mm/inch	260 x 270	10 ¹⁵ / ₈ " x 10 ⁵ / ₈ "
Min. Dimensions (W x H x L)	mm/inch	70 x 18 x 1000*	2 ³ / ₄ " x 4 ⁵ / ₆₄ " x 39 ³ / ₈ "

CONVEYOR BELT'S FEATURES

Useful Length	mm/inch	950	37 ¹³ / ₃₂ "
Total Length	mm/inch	1050	41 ¹¹ / ₃₂ "
Working Height	mm/inch	920	36 ⁷ / ₃₂ "
Electric Motor Power	kW	0,55	
Max. Conveyor Speed	meter/min.	36	
Max. Load Capacity	kgs/meter	100	

STRETCH FILM FEATURES

Max. Width	mm/inch	170	6 ¹¹ / ₁₆ "	
Max. Diameter	mm/inch	Ø 230	9 ¹ / ₁₆ "	(Max. Weight: 3 kg)
Reel Core Diameter	mm/inch	Ø 76	2 ⁶³ / ₆₄ "	
Recommended Thickness	micron	23, 30, 35		

MACHINE GENERAL FEATURES

Main Motor Power	kW	1,1	
Max. Ring Rotation Speed	rpm	140	
Min. Ring Rotation Speed	rpm	30	
*Electric Supply	Volt - Hz	380 Volt - 50/60 Hz - 3P+1N+1G	
Total Power	kW	2,3	
Standard Machine Dimensions (W x H x L)	mm/inch	1600 x 1664 x 2744	62 ⁶³ / ₆₄ " x 65 ³³ / ₆₄ " x 108 ¹ / ₃₂ "
Total Weight	kg	940	

* 208 Volt, 380 Volt, 415 Volt, 480 Volt 50/60 Hz (optional)

